

CERTIFICATE OF COMPLIANCE

Certificate Number 20150508-E98049
Report Reference E98049- 19991213
Issue Date 2015-MAY-08

Issued to: BENDER & WIRTH GMBH & CO
VOLMESTRASSE 161
58566 KIERSPE GERMANY

This is to certify that representative samples of COMPONENT - LAMPHOLDERS, MISCELLANEOUS (USR/CNR) Component - Lampholders, Miscellaneous, Cat. Nos. 985, 985P, and 985M.

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 496 Lampholders
CSA-C22.2 No. 43 Lampholders

Additional Information: See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for use as components of complete equipment submitted for investigation rather than for direct separate installation in the field. The final acceptance of the component is dependent upon its installation and use in complete equipment submitted to UL LLC.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



DESCRIPTION

PRODUCT COVERED:

(USR/CNR) Component - Lampholders, Miscellaneous, Cat. Nos. 985, 985P, and 985M.

USR indicates investigated to US requirements, UL 496

CNR indicates investigated to Canadian requirements, C22.2 No. 43

ENGINEERING CONSIDERATIONS (NOT FOR UL REPRESENTATIVE USE):

Use - The devices covered by this Report are for use only in complete equipment where the suitability of the combination is determined by Underwriters Laboratories Inc. The following should be ascertain in the end-use product.

Conditions of Acceptability -

1. The lampholder shall be used within its electrical rating.
2. Spacings of live parts shall meet the spacing requirements of the end use application.
3. All live parts shall be suitably enclosed in the end use application.

CONSTRUCTION DETAILS:

The general design, shape and arrangement shall be as shown except where variations are specifically described. All dimensions are approximate unless otherwise indicated.

Spacings - Min 3.2 mm through air and over surface between uninsulated live parts of opposite polarity and between uninsulated live parts and dead-metal parts.

Corrosion Protection - All ferrous metal parts are protected from corrosion by painting, plating or the equivalent.

ELECTRICAL RATINGS

For Model 985 and 985P - 750 V, 20 A, pulse rated 5 kV.

For Model 985M - 250 V, 20 A, pulse rated 5 kV.

Markings:

Marking - R/C name or trademark and electrical ratings on device or catalog number and electrical rating on shipping carton.